PRODUCT INFORMATION SHEET

Product Name: **2 STROKE TCW-3**
OUTBOARD ENGINE OIL

PRODUCT

Bimrose 2 Stroke TC-W3 is a special two-stroke oil formulated from high quality base
oils and an excellent additive package in order to meet the strict requirements of the National Marine Manufacturers Association TC-W3 standard. The base oil selection ensures virtually smokeless operation. This product provides superior performance in water cooled two-stroke engines (pre-mix or oil injected) and has a selected lubricity enhancer.

Viscosity	Typical 8.5 cSt @ 100^{o}C

APPLICATION

Recommended for all water-cooled two-stroke marine engines where the manufacturer requires a lubricant meeting the TC-W3 standard. 2 Stroke TCW-3 can be used with fuel/oil ratios of up to 100:1 (mix as per engine manufacturers recommendation).

STANDARDS

Meets or exceeds the following:
NMMA (BIA): TCW-3, TCW-II
API: TD (TSC-4).

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres, 1 Litres.

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinacle Street,
Brendale, Qld. 4500.

Telephone: (07) 3881 1733
Fax: (07) 3881 1708
Email: admin@prolube .com.au
Internet: www.bimrose.com.au

Issue Date 20/1/2017