



PRODUCT INFORMATION SHEET

Product Name: HEAVY 40 ENGINE OIL

PRODUCT

Bimrose Heavy 40 Engine Oil is a SAE 40 oil originally developed to meet the Caterpillar Series 3 and Alison C3 requirements. It is recommended also for use in GM Detroit diesel engines, which require oil with a low sulphated ash residue. It can be used in petrol and diesel engines where monograde oil is preferred. It can be used also as hydraulic oil for earthmoving machinery.

Viscosity Typical 11.5 cSt @ 100°C

APPLICATION

Designed for engines, transmissions and hydraulic systems where SAE 30 monograde oil is specified or indicated. It is particularly suitable for older style diesel motors that may react unfavourably to modern, multigrade engine oils. Its primary recommendation is as a running-in oil for rebuilt and reconditioned petrol and diesel motors subject to manufacturer's specification.

STANDARDS

Meets or exceeds the following:
SAE Grade: SAE 40
API: CD SF

CONTAINER SIZES

205 Litres, 60 Litres, 20 Litres, 5 Litres.

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.bimrose.com.au

Issue Date 10/1/2017