



**PRODUCT INFORMATION SHEET**

**Product Name: LIM SLIP 90 and 85W140 GL5**

**PRODUCT**

Bimrose Lim Slip 90 and Lim Slip 85W140 are special products that are used in certain types of limited slip differentials. As well as meeting all normal requirements for SAE 90 and 85W140 gear oils, they have a special supplement that enhances their performance as a rear axle lubricant. The premium additive pack provides excellent anti-wear, anti-corrosion, anti-oxidisation and extreme pressure protection and allows use in normal gear applications and enhanced performance in limited slip differentials.

Grade	LS 90	LS 85W140
Viscosity (Typical cSt @ 40°C)	148	350
Viscosity (Typical cSt @ 100°C)	15	25.5

**APPLICATION**

These gear oils are designed for passenger vehicles, light trucks, heavy trucks and off-road equipment fitted with limited slip differentials.

**STANDARDS**

Meets or exceeds the following specifications or is suitable for use :  
SAE Grade: 80W90, SAE 90 - SAE 140, 85W140.  
API: GL5  
MACK: GO-J  
MIL-L-2105D MIL-PRF-2105E.  
ZF TE – ML 05C, 12C, 16E, 21C  
Arvin Meritor Axles

**CONTAINER SIZES**

205 Litres,                      60 Litres,                      20 Litres,                      5 Litres.

**CONTACT**

***BIMROSE Lubricants,***

P.O. Box 5435,  
15 Pinnacle Street,  
Brendale, Qld. 4500.

Telephone: (07) 3881 1733  
Fax: (07) 3881 1708  
Email: admin@prolube.com.au  
Internet: [www.bimrose.com.au](http://www.bimrose.com.au)

Issue Date 23/1/2017