



PRODUCT INFORMATION SHEET

Product Name: MULTIGRADE 15W50 SL CF

PRODUCT

Bimrose Multigrade 15W50 engine oil has modern technology for late model, high stress applications. It provides the maximum protection against wear, corrosion, oxidation and sludge formation and is particularly suitable for naturally aspirated and turbo-charged models. HVX MS oil can be used in light and medium duty diesel engines and it provides enhanced valve train lubrication in modern unleaded petrol and LP gas motors. This product is also suitable for four stroke motorcycles fitted with wet clutches.

Viscosity Typical 18.3 cSt @ 100°C

APPLICATION

This oil is designed for all 4 stroke and rotary petrol motors using LP, ULP, PULP and LP gas fuels and requiring an SAE 15W50 engine oil. Although it was specifically designed for post-1997 model motors, including multi-valve and turbo-charged motors, it is also suitable for light duty passenger car style diesel motors.

STANDARDS

Meets or exceeds the following:

SAE Grade: 15W50
API: SL CF
ACEA: A3 / B3-04
MB 229.1 VW 505 00
JASO MA

CONTAINER SIZES

205 Litres

CONTACT

PROLUBE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.bimrose.com.au

Issue Date 20/1/2017