



## PRODUCT INFORMATION SHEET

**Product Name: NEW GENERATION 15W40**

### PRODUCT

Bimrose New Generation 15W40 has been formulated using new generation high performance base oils and the most recent additive technology to meet the latest CI-4 performance requirements. Ultrafleet 15W40 provides optimum protection and control of corrosion, oil thickening due to soot build up, piston deposits, oxidation, sludge build up and high temperature stability.

Viscosity (Typical)	15.0 cSt @ 100°C 124 cSt @ 40°C
Viscosity Index	123
TBN	10.12 mg KOH/g
Sulphated Ash	1.42 mass/wt-%

### APPLICATION

New Generation is a high performance mixed fleet lubricant designed for use in the latest European, US and Japanese four stroke diesel engines, including the new breed highly turbocharged and emission control designed engines. New Generation is our primary recommendation for electronically controlled engines, where high soot loading is experienced and for extended drain or severe service conditions. Extended drain intervals should be in compliance with the engine manufacturer guidelines and in conjunction with oil analysis checks.

### STANDARDS

Meets or exceeds the following or is recommended for:

SAE Grade: 15W40	API CI-4, CH-4/SL, SJ
CUMMINS CES 20076, 77, 78	Mack EO-M PLUS
ACEA: 08 E7 07 E7/B4/A3 04 E7/B4/B3/A3 02 E5/E3/B4/B3/A3	
Mercedes MB 228.2 228.3	Volvo VDS 3
Renault RLD2	MAN 3275
MTU Type 2	CAT ECF 1a, ECF-2

### CONTAINER SIZES

Bulk, 205 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre.

### CONTACT

#### ***BIMROSE Lubricants,***

P.O. Box 5435,  
15 Pinnacle St,  
Brendale, Qld. 4500.

Telephone: (07) 3881.1733  
Fax: (07) 3881.1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.prolube.com.au](http://www.prolube.com.au)