PRODUCT INFORMATION SHEET

Product Name: SELF LEVELLING MACHINERY GREASE

PRODUCT

Bimrose Self Levelling Machinery Grease is a general-purpose lithium extreme pressure (EP) grease with anti-wear performance. It has outstanding rust and corrosion protection and excellent resistance to water washout.
It is manufactured with a lithium hydroxy- stearate soap base with selected high viscosity index mineral oils combined with rust, oxidation and corrosion inhibitors and very effective lead free extreme pressure additives.

Appearance	Light brown, semi fluid	
Worked Penetration	415 mm	ASTM D217
Oil Viscosity	180 cSt@40^{o}C Typical	
Timken OK Load	D23	ASTM D2509
4 Ball Weld Test	290 kg	ASTM D2596

APPLICATION

This grease is used in gearboxes and bearings in mobile machinery where the grease needs to flow to the point of application. It is also used in gearboxes where sealing is poor or where seals are worn and gear oils cannot be retained. The grease has excellent lubrication qualities and is ideal for pumping or for use in once through centralised automatic or semi automatic lubrication systems.

The recommended temperature range is from -20 ^{o}C to 130 ^{o}C, however Self Levelling Grease may be used at higher temperatures with the lubrication frequency increased accordingly.

STANDARDS

NLGI Grade No 00

CONTAINER SIZES

20 kg 2.5 kg

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube .com.au
Internet: www.bimrose.com.au

Issue Date 23/1/2017