PRODUCT INFORMATION SHEET

Product Name: **SUPER RED LITHTAC GREASE**

PRODUCT

Bimrose Super Red Lithtac Grease is an extremely high quality product with excellent lubrication characteristics for the range of anti-friction and plain bearings, gears and couplings in automotive, marine, agricultural and industrial applications requiring a grease with a high base oil viscosity and weld load. It is based on a lithium complex thickener, high quality paraffinic and polybutene base stocks combined with the inclusion of extreme pressure additives, effective rust, oxidation and corrosion inhibitors.

Appearance	Red, Smooth and Tacky	
Worked Penetration	270 mm	ASTM D217
Oil Viscosity - Typical	1900 cSt@40^{o}C	
Timken OK Load	30	ASTM D2509
4 Ball Weld Test	480 kg	ASTM D2596

APPLICATION

Bimrose Super Red Lithtac Grease is the ideal recommendation for use in extreme heavy-duty applications and where high thermal resistance is a must. These applications include all industrial, earthmoving, agricultural, automotive and marine equipment.
Super Red Lithtac Grease is also suitable for high shock load applications such as excavator and loader bucket pins.

The recommended temperature range is from -20 ^{o}C to 185 ^{o}C, however Super Red Lithtac Grease may be used at temperatures to 200^{o}C with the lubrication frequency increased accordingly.

STANDARDS

NLGI Grade No 2

CONTAINER SIZES

20 kg 2.5kg 450 gr Cartridges.

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube .com.au
Internet: www.bimrose.com.au

Issue Date 23/1/2017