



## PRODUCT INFORMATION SHEET

**Product Name: TURBO 15W50**

### PRODUCT

Bimrose Turbo 15W50 combines the very latest additive technology and high quality base oils to provide a lubricant with exceptional performance in the latest model turbo charged diesel and petrol engines. This product ensures less oil thickening; better oxidation and corrosion resistance, less wear and improved all-round performance. It is recommended for mixed fleet service where late model vehicles are in use, particularly where they work under hot or adverse conditions.

Viscosity Typical 18.55 cSt @ 100°C

### APPLICATION

Designed for 4 stroke motors using LP, ULP, PULP, LPG and diesel fuels particularly in high performance applications. It is specifically designed as an alternative to synthetic lubricants and as a means of maintaining component protection in high stress applications.

### STANDARDS

Meets or exceeds the following or is recommended for:  
SAE Grade: 15W50 API CI-4, CH-4/SL, SJ  
CUMMINS CES 20076, 77, 78 Mack EO-M PLUS  
ACEA: 08 E7 07 E7/B4/A3 04 E7/B4/B3/A3 02 E5/E3/B4/B3/A3  
Mercedes MB 228.2 228.3 Volvo VDS 3  
Renault RLD2 MAN 3275  
MTU Type 2 CAT ECF 1a, ECF-2

### CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres.

### CONTACT

***BIMROSE Lubricants,***

P.O. Box 5435,  
15 Pinnacle St,  
Brendale, Qld. 4500.

Telephone: (07) 3881.1733  
Fax: (07) 3881.1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.bimrose.com.au](http://www.bimrose.com.au)

Issue Date 20/1/2017