



PRODUCT INFORMATION SHEET

Product Name 75W90 GEAR DIFF OIL FULL SYNTHETIC

PRODUCT

Bimrose 75W90 GEAR DIFF OIL Full Synthetic is an extreme heavy-duty multi-application driveline lubricant featuring full blend synthetic technology. It has been formulated for manual gearboxes, transfer cases and differentials including standard, limited slip and locking types. It provides outstanding gear, synchroniser and bearing lubrication as well as excellent cold flow and gearshift quality. In addition, there is the potential to significantly extend drain cycles.

Viscosity

Typical 14.5 cSt @ 100°C

Typical 104 cSt @ 40°C

APPLICATION

This oil is designed for most automotive, transport and heavy equipment gear applications subject to equipment manufacturers' recommendations. It has been specifically designed for severe service high-heat, high-load and constant running commercial situations.

STANDARDS

SAE Grade: 75W90 API GL5

US Steel 224

MT-1 Cincinnati Milacron

MIL-L-2105D, MIL-PRF-2105E, SAEJ2360 AGMA 250.04

Mack GO-J

CONTAINER SIZES

205 Litres,

20 Litres.

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinnacle Street,
Brendale, Qld. 4500.

Telephone: (07) 3881 1733
Fax: (07) 3881 1708
Email: admin@prolube.com.au

Issue Date 23/1/2017