



PRODUCT INFORMATION SHEET

Product Name: DIESEL 15W40

PRODUCT

Bimrose Diesel 15W40 is very shear stable, provides excellent protection against wear, corrosion and oxidation and ensures a high degree of engine cleanliness. It is suitable for naturally aspirated and turbo-charged diesel and petrol engines including those running on unleaded petrol.

APPLICATION

Designed for 4 Stroke motors using ULP, PULP, LPG and Diesel fuels where a 15W40 engine oil is specified or indicated. It is specifically designed for pre-1997 North American-style diesel motors requiring low ash engine oils. The primary recommendation is for mixed fleet operations.

STANDARDS

Meets or exceeds the following:

SAE Grade:	15W40	API:	CG-4 SL
Mack:	EO-L	MTU	Type 2
ACEA:	E2/A3/B4	Volvo	VDS
MAN	M3275	Mercedes Benz	228.3/229.1

CONTAINER SIZES

Bulk, 205 Litres, 60 Litres, 20 Litres, 5 Litres.

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube.com.au
Internet: www.bimrose.com.au

Issue Date 20/1/2017