



## **PRODUCT INFORMATION SHEET**

**Product Name: FIRST FILL 30 CD SF**

### **PRODUCT**

Bimrose First Full 30 is a SAE 30 oil originally developed to meet the Caterpillar Series 3 and Alison C3 requirements. It is recommended also for use in GM Detroit diesel engines, which require oil with a low sulphated ash residue. It can be used in petrol and diesel engines where monograde oil is preferred. It can be used also as hydraulic oil for earthmoving machinery.

Viscosity    Typical 11.5 cSt @ 100°C

### **APPLICATION**

Designed for engines, transmissions and hydraulic systems where SAE 30 monograde oil is specified or indicated. It is particularly suitable for older style diesel motors that may react unfavourably to modern, multigrade engine oils. Its primary recommendation is as a running-in oil for rebuilt and reconditioned petrol and diesel motors subject to manufacturer's specification.

### **STANDARDS**

Meets or exceeds the following:

SAE Grade:	SAE 30
API:	CD SF

### **CONTAINER SIZES**

205 Litres,                          60 Litres,                          20 Litres,                          5 Litres.

### **CONTACT**

#### ***Bimrose Lubricants***

P.O. Box 5435,  
15 Pinnacle St,  
Brendale, Qld. 4500.

Telephone:	(07) 3881.1733
Fax:	(07) 3881.1708
Email:	admin@bimrose.com.au
Internet:	www.bimrose.com.au

Issue Date 18/1/2017