



## PRODUCT INFORMATION SHEET

**Product Name: SLWMO 10W30**

### PRODUCT

Bimrose Super Light Weight Motor Oil 10W30 is a heavily fortified oil which uses the latest additive technology to provide significantly better performance in late model petrol engines. It is suitable for naturally aspirated and turbocharged motors. It ensures better rust and corrosion protection, less oil oxidation and superior deposit control and wear protection. This product is particularly recommended where the manufacturer requires the use of a lighter multigrade oil or where vehicles encounter lower temperature operation, providing superior component protection at cold start-up.

Viscosity Typical 10.0 cSt @ 100°C

### APPLICATION

This oil is designed for late model 4-stroke petrol motors, particularly multi-valve, multi-cam models requiring lower viscosity oils for fuel economy, low emissions and high performance. It has been formulated for applications where 5W30 to 10W30 engine oils are specified.

### STANDARDS

Meets or exceeds the following:

SAE Grade: 10W30  
API: SL CF  
ACEA: A3 / B3  
ILSAC: GF2

### CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres, 1 Litre.

### CONTACT

#### ***BIMROSE Lubricants,***

P.O. Box 5435,  
15 Pinnacle St,  
Brendale, Qld. 4500.

Telephone: (07) 3881.1733  
Fax: (07) 3881.1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.bimrose.com.au](http://www.bimrose.com.au)

Issue Date 20/1/2017