



PRODUCT INFORMATION SHEET

Product Name: 5W20 FULL SYNTHETIC

PRODUCT

Bimrose 5W20 Full Synthetic is a fully synthetic motor oil formulated to meet the latest technical requirements of modern petrol and diesel engines. It is specifically targeted to the latest ILSAC and API requirements.

The modern additive technology provides excellent protection against engine and valve train wear, while controlling oxidation and catalytic converter fouling. Using synthetic oils provides exceptional fuel efficiency.

Viscosity

Typical 7.9 cSt @ 100°C

APPLICATION

Bimrose 5W20 Full Synthetic meets the requirements of ILSAC GF5 and API SN specifications, making it the recommendation for Chrysler, Ford and GM service fill. 5W20 Full Synthetic is also recommended where GM Dexos® 1 is specified.

STANDARDS

Meets or exceeds the following:

SAE Grade: 5W20

API SN, SM

ILSAC GF5

GM 6094M

Ford WSS-M2C-945A/946A

Chrysler MS 6395

CONTAINER SIZES

205 Litres,

20 Litres,

5 Litres.

CONTACT

Bimrose Lubricants,

P.O. Box 5435,
15 Pinnacle Street,
Brendale, Qld. 4500.

Telephone: (07) 3881 1733
Fax: (07) 3881 1708
Email: admin@prolube.com.au
Internet: www.bimrose.com.au

Issue Date 20/1/2017