



PRODUCT INFORMATION SHEET

Product Name: AUTOMAX CVT

PRODUCT

Bimrose Automax CVT is a high performance multivehicle transmission oil for modern vehicles with Continuously Variable Transmissions (CVT). It is blended with synthetic base stocks and specialised additives to give the appropriate friction characteristics required while still providing excellent anti-wear performance for the transmission componentry.

It extends transmission life by minimising wear, reduced deposit formations, longer service life due to the full synthetic base stocks and shear-stable additive technology.

Viscosity

Typical 8.0 cSt@100°C

APPLICATION

A multi-vehicle CVT fluid for use in the latest model American, European and Asian vehicles belt or chain drive CVTs. It is not suitable for use in Ford and Toyota Hybrid CVT such as in the Prius models.

STANDARDS

Meets the performance requirements of:

- Audi VW (TL 52180, G052 180, G052 516)
- Ford (CVT 30, Mercon C, CVT 23)
- Subaru (Lineartronic CVTF)
- Nissan (NS-1, NS-2)
- Mini Cooper (EZL 799A)
- Hyundai KIA (SP-CVT 1)
- Dodge Jeep (DEX-CVT)
- Honda (HMMF)
- Mitsubishi (CVTF-J1)
- Punch (EZL 799A)
- Suzuki (TC / NS-2 / CVT Green 1)
- MB (236.20)

CONTAINER SIZES

205 Litres

20 Litres

5 Litres

CONTACT

BIMROSE Lubricants,

P.O. Box 5435,
15 Pinnacle St,
Brendale, Qld. 4500.

Telephone: (07) 3881.1733
Fax: (07) 3881.1708
Email: admin@prolube
Internet: www.bimrose.com.au

Issue Date 23/1/2017