



## PRODUCT INFORMATION SHEET

**Product Name: TO 4/10, 4/30/ 4/50 4/60  
Transmission / Hydraulic Fluid**

### PRODUCT

Bimrose TO 4/10, 4/30 4/50 and 4/60 are sophisticated transmission oils which have been developed to meet a range of transmissions used in agricultural and off-road equipment. They meet the requirements of the very latest Caterpillar TO-4, Allison C4, Komatsu and also Eaton and Dana manual transmissions. These oils provide excellent resistance to oxidation and friction and have desirable seal swell characteristics.

	<b>410</b>	<b>30</b>	<b>450</b>	<b>460</b>
Viscosity (cSt @ 40°C Typ)	41	98	200	270
Viscosity (cSt @ 100°C)	6.4	11.6	18.7	24.5
SAE Viscosity	10	30	50	60

### APPLICATION

Bimrose TO 4/10 4/30 are the primary recommendations for Allison C4 (except "WT") and Caterpillar powershift transmissions.

Bimrose TO 4/50 4/60 is the primary recommendation for most heavy duty truck transmissions including Caterpillar, Fuller, Roadranger and Volvo.

### STANDARDS

Meets performance requirements of major off road transmission manufacturers including

Caterpillar:	TO4
Allison:	C-4
Komatsu	
Eaton/Fuller	
ZF:	TE-ML03/TE-ML01

### CONTAINER SIZES

205 Litres,                      20 Litres.

### CONTACT

***BIMROSE Lubricants,***

P.O. Box 5435,  
15 Pinnacle St,  
Brendale, Qld. 4500.

Telephone: (07) 3881.1733  
Fax: (07) 3881.1708  
Email: [admin@prolube.com.au](mailto:admin@prolube.com.au)  
Internet: [www.bimrose.com.au](http://www.bimrose.com.au)

Issue Date 23/1/2017