15 Pinacle Street Brendale QLD 4500 | Ph: (07) 49213 800 admin@prolube.com.au | www.bimrose.com.au

ABN: 64 010 867 428

PRODUCT DATA SHEET

75W140 FULL SYNTHETIC GEARBOX & DIFF OIL

DESCRIPTION

Bimrose 75W140 Synthetic Gearbox & Diff Oil is an extreme heavy-duty multi-application driveline lubricant featuring full blend synthetic technology. It has been formulated for manual gearboxes, transfer cases and differentials including standard, limited slip and locking types. It provides outstanding gear, synchroniser and bearing lubrication as well as excellent cold flow and gearshift quality. In addition, there is the potential to significantly extend drain cycles.

Viscosity Typical 27.0 cSt @ 100°C) Viscosity Typical 220 cSt @ 40°C)

APPLICATION

This oil is designed for most automotive, transport and heavy equipment gear applications subject to equipment manufacturers' recommendations. It has been specifically designed for severe service high-heat, high-load and constant running commercial situations.

STANDARDS

Meets or exceeds the following:

SAE Grade: 75W140 API GL5, GL4, MT-1 Arvin Meritor 0-76-N

MIL-PRF-2105E

Mack GO-J

Volvo 97312

MAN 342 M3, 341 Z2, 342 S1

DAF

Iveco

Renault

SAE J2360

Detroit Diesel DFS93K219.01

MB 235.8

Scania STO 1:0 STO 2:0A FS

ZF TE-ML 05A, 07A, 12N, 21A

Dana 40819

GM HN 2040

BTR 5M-48

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres

Issue Date: 27/2/2020