



PRODUCT DATA SHEET

75W90 FULL SYNTHETIC GEAR OIL GL5

DESCRIPTION

75W90 Full Synthetic Gear Oil is an extreme heavy-duty multi-application driveline lubricant featuring full blend synthetic technology. It has been formulated for manual gearboxes, transfer cases and differentials including standard, limited slip and locking types. It provides outstanding gear, synchroniser and bearing lubrication as well as excellent cold flow and gearshift quality. In addition, there is the potential to significantly extend drain cycles.

Viscosity Typical 16.5 cSt @ 100oC

Viscosity Typical 114 cSt @ 40oC

APPLICATION

This oil is designed for most automotive, transport and heavy equipment gear applications subject to equipment manufacturers' recommendations. It has been specifically designed for severe service high-heat, high-load and constant running commercial situations.

STANDARDS

Meets or exceeds the following:

SAE Grade: 75W90

API GL5, GL4, MT-1

Arvin Meritor 0-76-N

MIL-PRF-2105E

Mack GO-J

Volvo 97312

MAN 342 M3, 341 Z2, 342 S1

DAF

Iveco

Renault

SAE J2360

Detroit Diesel DFS93K219.01

MB 235.8

Scania STO 1:0 STO 2:0A FS

ZF TE-ML 02B, 05A, 07A, 12B, 12L, 12N, 16B, 16F, 17B, 19C, 21A

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres

Issue Date 1/5/2020