



PRODUCT DATA SHEET

AUTO TRANS FLUID DXIII

DESCRIPTION

Auto Trans Fluid DXIII is an Automatic Transmission Fluid formulated from high quality base oils blended with an excellent additive pack to provide a lubricant which meets the specific requirements of the GM Dexron® III specifications. Although Dexron® III is a General Motors specification for their vehicles, there are some hydraulic pump manufacturers who recommend the use of this fluid in their hydraulic pump applications.

Viscosity - Typical 6.0 cSt @ 100°C

APPLICATION

Designed for automatic transmissions, power steering systems, fluid drive systems and hydraulic systems where a Dexron® III fluid is specified.

STANDARDS

Meets or exceeds the following:

General Motors Dexron® III-H, III-G, III-F, III-E, III-D

Mercedes Benz 236.1, 236.5, 236.6, 236.7

ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C

Voith 55,6335 and 55,6336

Allison C4, TES 389

Caterpillar TO-2

Chrysler Transmissions (except where MS-9602 or MS-7 176 is specified)

Ford Mercon®, Ford M2C138-CJ, M2C 166-H Fluids

Volvo 97340, 97341

MAN 339 Z1, V1, Z2, V2

Sperry, Vickers, Denison and Sunstrand for hydraulic pump systems.

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres