



PRODUCT DATA SHEET

COMPRESSOR OIL 32 46 68 100 150

DESCRIPTION

Compressor Oil is blended from semi synthetic and highly refined virgin base oils, with ashless anticorrosion, anti-oxidisation and anti-wear additives. The product also has good anti-foam and excellent thermal resistance properties.

Grade	32	46	68	100	150
Viscosity (Typical cSt @ 40°C)	32	46	68	100	150
Viscosity (Typical cSt @ 100°C)	5.5	6.8	8.6	11.3	15.0
Viscosity Index	110	100	100	100	100
Specific Gravity	0.87	0.88	0.88	0.88	0.89
Rust Test (ASTM D665B)	Pass	Pass	Pass	Pass	Pass
CCR Oxidation (DIN 51352-2) % wt	0.7	0.7	1.0	1.5	2.0

APPLICATION

Suitable for use in all types of reciprocating air compressors and high performance drip feed rotary or screw compressors and vacuum pumps. A long service life can be expected in good conditions with a wide range of operating temperatures.

Can be used as an hydraulic oil in non severe applications.
Viscosity choice should be according to manufacturer's recommendations.

STANDARDS

Meets or exceeds the following:

DIN 51425 Part 2 (HLP) and Part 3 (HVLP)

AFNOR NF E48-603 HM and HV

Eaton Brochure 694 for 35VQ25A

DIN 51506 (VBL, VCL, VDL)

ISO / DP 6521 (DAA, DAB, DAH, DAG)

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres