



PRODUCT DATA SHEET

EURO SPECIAL 15W40 CK-4

DESCRIPTION

Euro Special 15W40 CK-4 is designed to meet and exceed the latest American Petroleum Institute (API) specifications, to deliver a superior performance multigrade engine oil, for use in modern four stroke diesel engines, including those fitted with EGR (exhaust gas reticulation) DPF (diesel particulate filter) or SCR/Adblue (selective catalytic reduction) systems. Euro Special 15W40 CK-4 is formulated for long haul extended drain cycle operations. Euro Special 15W40 CK-4 has exceptional performance as it is designed to combine the latest in diesel technology additive packages to provide superior anti-wear, anti-corrosion, anti-oxidant protection exceptional soot control and improved fuel economy. Being backwards compatible with the previous API versions, it is an ideal mixed fleet product while providing the best possible protection to the newest technology engines.

Viscosity (Typical 14.5 cSt @ 100°C)

Viscosity (Typical 110 cSt @ 40°C)

Viscosity Index - 135

TBN ASTM D2896 - 9.7 mg KOH/g

Sulphated Ash - 0.98 mass/wt-%

APPLICATION

Euro Special 15W40 CK-4 is recommended for all four stroke US built high performance heavy duty diesel engines turbo charged or naturally aspirated as well as many of the latest European and Japanese heavy-duty and light duty commercial diesel engines. Extended oil drain periods can be achieved with this ultimate performance product. Regular oil analysis will maximise your drain periods as well as provide you with valuable information to minimise the cost to your operation.

STANDARDS

Approvals:

CUMMINS: CES 20086

API: CK-4, CJ-4, CI-4, CI-4 Plus

CUMMINS CES 20076, 77, 78

Mack EO-S 4.5,

Volvo VDS-4.5

Caterpillar: ECF-3

Detroit: DFS 93K222

Renault Truck RLD-4



Bimrose Lubricants
15 Pinnacle Street Brendale QLD 4500 | Ph: (07) 49213 800
admin@prolube.com.au | www.bimrose.com.au
ABN: 64 010 867 428

STANDARDS con:

Meets or exceeds the following:

SAE Grade: 15W40

Cummins: CES 20081

Mack EO-O Premium Plus

Volvo VDS-4

Ford WSS-M2C171-F1

MTU Type 2.1

Detroit: DFS 93K218

ACEA E9-16, E7-16 (2016)

Renault Truck RLD-3

JASO DH2

MB 228.31

Deutz DQC III-10 LA

MAN 3575

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres