



PRODUCT DATA SHEET

FULL SYNTHETIC 10W50

DESCRIPTION

Full Synthetic 10W50 is a multi-function diesel/petrol/LPG engine oil incorporating the latest developments in synthetic lubricant technology. It provides enhanced engine component protection in high load, high performance and competition applications. There is the potential to significantly expand drain cycles and to achieve gains in fuel economy as well as an upgraded capacity to withstand extreme heat and humidity.

Viscosity - Typical 14.5 cSt @ 100oC
Typical 104 cSt @ 100oC

APPLICATION

This oil is designed for all 4-stroke motors using LP, ULP, PULP, LPG and diesel fuels including multi-valve, turbo-charged and super-charged models. It has been specifically designed for extended drain service intervals in extreme conditions and wide temperature variations. Oil analysis is recommended to achieve optimum drain periods.

STANDARDS

Meets or exceeds the following:

SAE Grade: 10W50

API: CI-4, SL / CH-4, SJ

ACEA: E7-08 A3, B3, B4-10

MB 228.3 229.1

Detroit Diesel DDC93K215

MTU Type 2

MAN 3275-1

Volvo VDS 3

Mack EO M Plus EO N

Cummins 20077/78

Renault RLD-2

Deutz DQC III-10

JASO DH1

Allison C4

Global DHD1

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres

Issue Date 1/5/2020