

15 Pinacle Street Brendale QLD 4500 | Ph: (07) 49213 800 admin@prolube.com.au | www.bimrose.com.au

ABN: 64 010 867 428

PRODUCT DATA SHEET

FULL SYNTHETIC 5W30 C1

DESCRIPTION

Full Synthetic 5W30 C1 is fully synthetic motor oil formulated to meet the specific fuel economy requirements of modern passenger car diesel engines with diesel particulate filters (DPFs). Full Synthetic 5W30 C1 is formulated with the latest Ultra Low SAPS additive technology to provide a stable, stay in grade product to meet the ACEA C1 specifications.

This product provides excellent fuel economy and protection against wear and oil oxidation to meet the longer oil drain requirements of many modern European diesels.

Viscosity Typical 9.7 cSt @ 100°C

APPLICATION

Full Synthetic 5W30 C1 is designed for use in high performance gasoline and light duty diesel engines where advanced after-treatment systems such as Diesel Particulate Filters (DPFs) and Three Way Catalysts (TWC) are used. 5W30 C1 meets the requirements of modern diesel powered vehicles requiring ACEA C1 specification lubricants. This especially applies to many European manufactured vehicles. 5W30 C1 is recommended for use where the manufacturer specifies a C4 type oil.

STANDARDS

Meets or exceeds the following:

SAE Grade: 5W30 ACEA C1-16 (2016) Ford WSS-M2C-934B MB 229.1 229.3

VW 501 01, 502 00, 505 00

Renault RN0700, 0710

PSA B71 2300

Jaguar Land Rover ST JLR.03.5003

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres