



PRODUCT DATA SHEET

FULL SYNTHETIC 5W30 C3

DESCRIPTION

Full Synthetic 5W30 C3 is a fully synthetic motor oil which uses the latest additive technology to provide significantly better performance in late model petrol and diesel engines. It is suitable for naturally aspirated and turbocharged motors. It ensures better rust and corrosion protection, less oil oxidation and superior deposit control and wear protection. This product is particularly recommended where the manufacturer requires the use of lower viscosity multigrade oil or where vehicles encounter lower temperature operation, providing superior component protection at cold start-up.

Viscosity Typical 11.0 cSt @ 100oC

APPLICATION

This oil is designed for late model 4 stroke petrol and engines, particularly multi-valve, multi-cam models requiring a low viscosity oil for fuel economy, low emissions and high performance. It is also ideal for modern car and SUV diesel engines. It has been formulated for applications where 5W30 to 10W30 engine oils are specified. Suitable for passenger vehicles fitted with Diesel Particulate Filters (DPF).

STANDARDS

Meets or exceeds the following:

SAE Grade: 5W30

API: SM, SN, CF

ACEA: C3-16 (2016) C2-16

MB 229.31, MB 229.51, MB 229.52

VW 505 00, 505 01, 502 00

BMW Longlife 4

Porsche

PSA B712290

JASO MA

Jaguar Land Rover ST JLR.03.5004

Ford WSS-M2C948-B

Suitable for use where GM Dexos 2 ® is specified

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres