



PRODUCT DATA SHEET

FULL SYNTHETIC A5B5 5W30

DESCRIPTION

Full Synthetic A5B5 5W30 is a fully synthetic motor oil designed for use in high performance gasoline and light duty diesel engines that are specifically designed to use a low viscosity oil. This high SAPS product provides excellent fuel economy and protection against wear and oil oxidation to meet the longer oil drain requirements of many modern European, Korean and Japanese vehicles.

Viscosity Typical 9.9 cSt @ 100°C

APPLICATION

Full Synthetic A5B5 5W30 is designed for use in high performance gasoline and light duty diesel engines which require oils meeting ACEA A5B5 specifications. This oil is an energy conserving, "low viscosity" type engine oil formulated to give the maximum performance in current technology engines.

It also meets the requirements for approved against Ford specification WSS-M2C913-D for additional fuel economy benefits in Ford engines used in all current Ford cars plus many Volvo, Jaguar and Land-Rover.

It is unsuitable for some engines especially where diesel particulate filters are fitted – consult owner manual or handbook if in doubt.

STANDARDS

Meets or exceeds the following:

SAE Grade: 5W30

ACEA A3/B3-16, A3/B4-16, A5/B5-16 (2016)

Ford WSS-M2C-913D / WSS-M2C-913C

MB 229.1 229.3

VW 501 01, 502 00, 505 00

Renault RN0700, 0710

PSA B71 2300

Jaguar Land Rover ST JLR.03.5003

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres