



PRODUCT DATA SHEET

FULL SYNTHETIC EUROTEC 5W30

DESCRIPTION

Full Synthetic Eurotec 5W30 is a fully synthetic motor oil formulated to meet the latest technical requirements of a wide variety of modern petrol and diesel engines. Incorporating the latest SAPS (Sulphated Ash, Phosphorous and Sulphur) additive technology, it is suitable for a wide variety of today's FSI, TDI and Turbocharged engines. Using synthetic oils provides exceptional fuel efficiency.

Viscosity Typical 12.0 cSt @ 100oC

APPLICATION

Full Synthetic Eurotec 5W30 is recommended for applications requiring VW 504.00 (Petrol Engines) and VW 507.00 (Diesel Engines), plus the latest Mercedes Benz and BMW specifications. It also meets the ACEA C3-16 (16 specification required for Diesel engines fitted with Diesel Particulate Filters (DPF), Catalytic Convertors and three way Catalyst (TWC).

This oil meets the Japanese JASO DL-1 specification, required for many Japanese diesel passenger cars.

STANDARDS

Meets or exceeds the following:

SAE Grade: 5W30

ACEA: C3-16

MB 229.51

VW 504 00, 507 00

BMW Longlife 4

Porsche C30

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres