

15 Pinacle Street Brendale QLD 4500 | Ph: (07) 49213 800 admin@prolube.com.au I www.bimrose.com.au

ABN: 64 010 867 428

PRODUCT DATA SHEET

LIM SLIP 140 GL5 LS

DESCRIPTION

Lim Slip 140 GL5 LS is a special product that is used in certain types of limited slip differentials. As well as meeting all normal requirements for SAE 90 and 85W140 gear oils, it has a special supplement that enhances the performance as a rear axle lubricant. The premium additive pack provides excellent anti-wear, anti-corrosion, anti-oxidisation and extreme pressure protection and allows use in normal gear applications and enhanced performance in limited slip differentials.

Viscosity Typical 25.5 cSt @ 100oC Viscosity Typical 350 cSt @ 40oC

APPLICATION

This gear oil is designed for passenger vehicles, light trucks, heavy trucks and off-road equipment fitted with limited slip differentials.

STANDARDS

Meets or exceeds the following:

SAE Grade: LS85W140

API: GL5 MACK: GO-J

MIL-PRF-2105D MIL-PRFP2105E ZF TE - ML 05C, 12C, 16E, 21C

Arvin Meritor Axles

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres