



PRODUCT DATA SHEET

TRACTOR HYDRAULIC TRANSMISSION FLUID

DESCRIPTION

THTF is a high performance Tractor Transmission and Hydraulic Fluid, blended to meet the requirements of most modern Tractors and is suitable for application where manufacturers specify a Tractor Transmission Fluid. THTF also provides excellent frictional characteristics necessary to eliminate brake chatter or squawk in wet brakes.

THTF has the added bonus of a corrosion inhibition package to coat and protect internal metal surfaces in periods of shut down such as between seasons.

Viscosity - Typical 10.5 cSt @ 100°C

APPLICATION

This fluid is designed for use in tractors requiring a common lubricant for transmission, final drive, hydraulics and wet brakes. It has been formulated for temperate to hot conditions where sustained thermal stability is essential.

STANDARDS

Meets performance requirements of major off-road transmission manufacturer including:

API	GL4 80W
Allison	C4
AGCO	Powerfluid 821XL, Q-186 (White Farm)
Ford/New Holland	ESN-M2C134-D, ESN-M2C86-B/C, FNHA-2-C-200.00 / 201.00
Massey Ferguson	CMS M1135, CMS M1141, CMS M1143, CMS M1145
John Deere	JDM J20C, J20D
Case	MS1207, MS1209, MS1210, MS1230
Case New Holland	CNH MAT3505, MAT3506, MAT3509, MAT3510, MAT3525, MAT3526, MAT3540
ZF	TE-ML 05F, 03E, 06E,F,K, N, R, 17E, 21F
Volvo VCE WB 101, 102	Fendt Vario, Non Vario
Deutz-Fahr	Landini
Class (Renault Transmissions)	Same (Same Transmissions)
Kubota UDT Fluid HCE 102 / 102W	Caterpillar TO-2

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres

Issue Date: 27/2/2020