



PRODUCT DATA SHEET

TRANSMISSION FLUID TO4 10 30 40 50 60

DESCRIPTION

Transmission Fluid TO4 10, 30 50 and 60 are sophisticated transmission oils which have been developed to meet a range of transmissions used in agricultural and off-road equipment. They meet the requirements of the very latest Caterpillar TO-4, Allison C4, Komatsu and also Eaton and Dana manual transmissions. These oils provide excellent resistance to oxidation and friction and have desirable seal swell characteristics.

Grade	10	30	50	60
Viscosity (cSt @ 40°C Typ)	41	98	200	300
Viscosity (cSt @ 100°C)	6.4	11.6	18.7	24.1
SAE Viscosity	10	30	50	60

APPLICATION

Transmission Fluid 10/30 are the primary recommendations for Allison C4 and Caterpillar powershift transmissions.

Transmission Fluid 50/60 is the primary recommendation for most heavy-duty truck transmissions including Caterpillar, Fuller, Roadranger and Volvo.

STANDARDS

Meets performance requirements of major off-road transmission manufacturer including:

Caterpillar:	TO4 (TO-2 obsolete)
Allison:	C-4
Komatsu Dresser	KES 07.868.1
Eaton/Fuller	
ZF:	TE-ML03C TE-ML07F
Dana	Powershift
Eaton Vickers	35VQ-25 Vane Pump Test
Tremac TTC (SAE 50 only)	

CONTAINER SIZES

205 Litres, 20 Litres, 5 Litres